

Invisible ultra mat finish for parquet and wooden floorings

Characteristics

Nature Protect 2K allows for the wood to maintain its natural colour and look, the treated wood will be extremely resistant to household chemicals and very hard-wearing.

Applications

An almost invisible, ultra mat finish for parquet and wooden floorings, walls, ceilings and furniture made of oak wood.

Base

2-Component Acrylat Polyurethan.

Technical data (after mixing)

Working temperature: 10 to 25°C. Do not use below 8°C.

Dust dry: 1 - 3 hours (at 60% relative humidity and at 20°C).

Drying time: 4 hours.

Hardening time: 7 days.

Potlife: about 3 hours.

Gloss (600): ultra mat < 5%.

Usage: about 2,5 litres of finish per 10 m² in two or three layers.

Cleaning tools: in water.

Storage: dry and away from frost.

Maintenance: Floorservice Parquet Polish mat.

Packing: 910 ml component A + 90 ml component B

EU-limit for this product (cat. A/j) 140 g/l (2010).

This product contains max. 70 g/l VOC

Instructions for use

Shake Nature Protect 2K (component A) well.

Then thoroughly mix 90 ml Curing Agent (component B) with 910 ml Nature Protect 2K (component A) (1:10). The ground surface must be well sanded, dry, free of dust and grease. Apply the finish with a varnish roller or a soft brush. First against the grain, then along the grain. Allow the strips to flow into each other. Apply a second and if required a third layer in the same way after a drying time of about 4 hours. Roughen the surface slightly between the layers.

Above product information and recommendations are given in good faith and based on practical tests following long term research and development. We cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. In cases of doubt always test the product in advance.

01.01.2013

